

Pony Trailed Sprayer



Pony Trailed Sprayer

ORDER CODE	DESCRIPTION	\$ (EX. GST)	\$ (INC. GST)	PROD. CAT.
BT-1000	1000 Litre Pony trailed sprayer c/w 1000 litre tank, galvanised chassis, single axle (suspended), AR70 PTO-drive twin-diaphragm pump (0-20 bar), ARUCM 4-tap manual control unit, 30 litre hand-wash tank	11,665.00	12,831.50	X
BT-1200	As above, but with 1200 litre tank in lieu of 1000L	11,780.00	12,958.00	X
BT-1500	As above, but with 1500 litre tank in lieu of 1000L	12,890.00	14,179.00	X

Pony Trailed Sprayer Options

ORDER CODE	DESCRIPTION	\$ (EX. GST)	\$ (INC. GST)	PROD. CAT.
SAL901654A	Double-sided foam marker (more detail P9)	1,194.56	1,314.02	X
SAL901658A	Single-sided foam marker (more detail P9)	750.00	825.00	X
MF08	8 metre Fieldmaster boom (more detail P6)	1,422.30	1,564.53	X
MF10	10 metre Fieldmaster boom (more detail P6)	1,719.30	1,891.23	X
MF12	12 metre Fieldmaster boom (more detail P6)	2,288.00	2,516.80	X
MA10	10 metre Acremaster boom (more detail P6)	2,838.00	3,121.80	X
MA12	12 metre Acremaster boom (more detail P6)	2,977.70	3,275.47	X
AR115-C	AR115 pump in lieu of AR70 pump	340.00	374.00	X
AR70-5H	AR70 Honda-powered motorised pump in lieu of AR70 PTO-drive	1,949.00	2,143.90	X
AR115-5H	AR115 Honda-powered motorised pump in lieu of AR70 PTO-drive	2,222.00	2,444.20	X
I-E2032	3-section electric boom control with electric pressure adjustment & master on/off switch, in-cab console (more detail page 26)	2,110.19	2,321.21	X
GB360589000V	1200mm Hydraulic height adjuster	2,382.53	2,620.78	X
GB380599000V	Self-leveling device with manual lock for Acremaster booms	1,755.30	1,930.83	X

Pony Trailed Sprayer Specifications

TANK	Translucent white UV-stabilised tank with calibrated markings. Large, hinged filling lid with basket strainer. Venturi & bypass agitation. 30L handwash tank fitted.
CHASSIS	Galvanised one-piece box-section multi-rail chassis with suspension axle & tow-hitch. Step provided for top fill access.
BOOMS	Manual fold booms to 12 metres, fully galvanised with single non-drip nozzle bodies and AirMix Air-induction nozzles fitted.
FILTRATION	Triple filtration – lid strainer, suction filter, nozzle filters (and pressure filter with electric controls as standard).
WHEELS	31 x 10.50R15LT tyres on Landcruiser rims.
PUMPS	Standard with AR70 (72 L/min, 0-20 bar) oil-bath twin-diaphragm pump, PTO drive. Optional AR115 (114 L/min) oil-bath triple-diaphragm pump, PTO drive. Both pump models also have a Honda-powered motorised option.
CONTROLS	Standard with ARUCM manual 4 way pressure relief valve with pressure adjustment and mater on/off lever. Optional electric controls available.
OPTIONAL EQUIPMENT	(Refer table above)